



BMR 600 VEHICLE

www.eraf.com

SPE \square

GENERAL	
♦ Basic Vehicle	6X6 Armor Vehicle
Configuration	Wheeled Troop Carrier
♦ Gross Vehicle Weight	15400 Kg
♦ Curb Weight	12000 Kg
Payload	3400 Kg
♦ Wheel Base	2300 mm
♦ Length	6150 mm
♦ Width	2500 mm
♦ Height	2000 mm
♦ Ground Clearance	400 mm
Max Speed on roads	95 km/h
Crew and Passenger	1+8
 Suspension Front 	Independent on Each Wheel
Suspension Rear	Independent on Each Wheel
♦ Number of Driven Шheels	6
Power Steering	All wheels Power assisted

Transmission Axles & Wheels	
Transmission Make And Model	ZF HP 500 6 speed automatic
Transmission Selection	Automatic
♦ Transfer Case Make And Model	N/A
Transfer Case Selection	N/A
 Front Axle 	Independent Wishbone
	Hydaraulic with Coil Spring
♦ Rear Axle	Independent Wishbone
	Hydaraulic with Coil Spring
♦ Wheels	Michellin 14.00R20XS

Configuration

Alluminum Monocoque Hull

STANUARU EQUIPMENT
♦ On-board tools
♦ 385 litre fuel tank
Manual fire extinguisher
Communication system

- ♦ Air Conditioning
- ♦ Heating
- ♦ Шinch
- ♦ Height adjustable Steering Wheel



Head Office: Al-Ahsa Street P.O.Box 27021, Riyadh 11417, T: + 966 11 2148078 F: + 966 11 4760989 E: eraf@eraf.com | www.eraf.com

Engine	
Make	SCANIA
Model	DS-61A1.00
♦ Fuel Supply	Common Rail Diesel
♦ Max Gross Power	228кш@2200 грт
♦ Max Gross Torque	1160Nm@1450 rpm

Accessories	
 Navigation System 	

- Automatic fire-detection and extinguisher
- $\$ Automatic fire and explosions detection and extinguishing systemin the crew compartment
- NBC protection system
 - Night vision equipment

GPS