



SANDCAT VEHICLE

шшш.eraf.com

SPECIFICATIONS SANIDE AT

SANDCAT VEHICLE

GENERAL	
Basic Vehicle	Armoured Toyota Landcruiser Pick Up
♦ Configuration	Armoured Cab on OEM Chassis
♦ Gross Vehicle Weight	6500 Kg
♦ Curb Weight	5000 Kg
♦ Payload	1500 Kg
♦ Wheel Base	2850 mm
♦ Length	5182 mm
♦ Width	2338 mm
♦ Height	2315 mm
♦ Ground Clearance	254 mm
♦ Max Speed on roads	120 Km/h
◆ Crew and Passenger	2 + 1
♦ Suspension Front	Leaf springs with gas dampers
♦ Suspension Rear	Leaf springs with gas dampers
Number of Driven Wheels	4
◆ Power Steering	Standard

Transmission Axles & Wheels	
Transmission Make And Model	Toyota FZJ80
Transmission Selection	Manual
♦ Transfer Case Make And Model	Toyota Integrated to Transmission
♦ Transfer Case Selection	Manual
♦ Front Axle	Toyota
	Rigid Axle
♦ Rear Axle	Toyota
	Rigid Axle
♦ Wheels	295/70R18 With RFI

HULL	
♦ Configuration	Bolted onto chassis all steel hull
	Protected up to BS EN 1522 FB6

STANDARD EQUIPMENT

- ♦ Run Flat Inserts
- ♦ Roof Escape Hatch
- ♦ Gun ports
 - Air conditioner

Engine	
♦ Make	Toyota
♦ Model	D-4D
♦ Fuel Supply	Direct Injection Diesel
♦ Max Gross Power	286Hp (212Kш) @ 3,600rpm
♦ Max Gross Torque	650Nm @1,600 - 2,800 rpm

Accessories

- ♦ Weapons Turret
- ♦ Electrical Winch
- Fire Suppression System
 - ♦ Communications System



Head Office: Al-Ahsa Street P.O.Box 27021, Riyadh 11417,

T: + 966 11 2148078 F: + 966 11 4760989

E: eraf@eraf.com | www.eraf.com