



CHEVROLET SUBURBAN

www.eraf.com

SPECIFICATIONS CHEVROLET SUBURBAN V3

GENERAL	
♦ Basic Vehicle	Chevrolet Suburban 4WD 2500 LS
Configuration	4 × 4
♦ Gross Vehicle Weight	3.373 tonnes
♦ Curb Weight	2123 tonnes
Payload	1.250 tonnes
♦ Wheel Base	Four (4) run-flat wheel
♦ Length	223 in (566 cm)
♦ Width	79 in (201 cm)
♦ Height	76 in (193 cm)
♦ Ground Clearance	220 mm
Max Speed on roads	140 km/h
♦ Crew and Passenger	2+2+2
 Suspension Front 	Short and Long Arm Suspension
♦ Suspension Rear	Solid Live Axle Suspension
♦ Number of Driven Wheels	4
Power Steering	Standard

Transmission Axles & Wheels	
Transmission Make And Model	
Transmission Selection	6-Speed Automatic
♦ Transfer Case Make And Model	NA
Transfer Case Selection	NA
♦ Front Axle	NA
♦ Rear Axle	NA
♦ Wheels	17/18" Aluminum-Alloy

HULL

Configuration

Armored to Level A9/B6+ Against 7.62x39, 5.56x45, 7.62x51, M193, & M80 Ball

STANDARD EQUIPMENT
♦ 200I Protected Fuel Tank
♦ Escape Hatch
♦ 7 Gun ports
♦ Provision for BAE ROШ
♦ Safari Roof
Cruise Control

- HD Air Conditioning System
 - ♦ ABS Brakes



Head Office: Al-Ahsa Street P.O.Box 27021, Riyadh 11417, T: + 966 11 2148078 F: + 966 11 4760989 E: eraf@eraf.com | www.eraf.com

Engine	
Make	Chevrolet
Model	Gas V8 6.0L/366
♦ Fuel System	Gas Engine / Sequential Electronic Fuel Injected,
	Sequential Port Fuel Injected Sequential,
	Multi-Port Fuel Injected
♦ Max Gross Power	352 @ 5400
🚸 Max Gross Torque	382 a 4200

- Accessories
- ♦ GPS System
- \diamondsuit Auxiliary Alternator for ancillaries
- ♦ First Aid Hit
- $\$ Hydraulic Jack And Vehicle Tools